



FILTRATION GROUP Tanktop return filter type Pi 5000 small

Characteristics

Series: Pi 5000

Temperature range [°C]: -10 / 80 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522655
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522650
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522657
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522659
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522639
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522658
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522656
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522651
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522653
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522654
	40		1" BSP cyl.	Bypass 3,5 bar	Optic		13522652
	40		1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522646
Pi 50004-050	40	10	1" BSP cyl.	Bypass 3,5 bar	Electrical 2,2 bar	250VAC/200VDC	13522638
Pi 50004-056	40	10	1" BSP cyl.	Bypass 3,5 bar	No		13522640
Pi 50004-047	40	10	1" BSP cyl.	Bypass 3,5 bar	No		13522637
Pi 50004-081	40	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522649
Pi 50004-059	40	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522643
Pi 50004-080	40	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522648
Pi 50004-076	40	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522644
Pi 50004-077	40	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522645
Pi 50004-057	40	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522641
Pi 50004-079	40	10	1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522647
Pi 50004-058	40	10	1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522642
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522699
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522701
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522694
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522697
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522704
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522684
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522696
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522702
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522703
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522695
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522700
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522705
	63		1" BSP cyl.	Bypass 3,5 bar	Optic		13522698
	63		1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522691
	63		1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522693
	63		1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522692
Pi 50006-052	63	10	1" BSP cyl.	Bypass 3,5 bar	Electrical 2,2 bar	250VAC/200VDC	13522685

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
Pi 50006-056	63	10	1" BSP cyl.	Bypass 3,5 bar	No		13522686
Pi 50006-047	63	10	1" BSP cyl.	Bypass 3,5 bar	No		13522683
Pi 50006-059	63	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522689
Pi 50006-057	63	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522687
Pi 50006-076	63	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522690
Pi 50006-058	63	10	1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522688
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522750
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522748
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522746
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522741
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522742
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522751
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522743
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522747
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522744
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522745
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522730
	100		1" BSP cyl.	Bypass 3,5 bar	Optic		13522749
	100		1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522736
	100		1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522737
	100		1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522739
	100		1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522738
Pi 50010-052	100	10	1" BSP cyl.	Bypass 3,5 bar	Electrical 2,2 bar	250VAC/200VDC	13522731
Pi 50010-047	100	10	1" BSP cyl.	Bypass 3,5 bar	No		13522729
Pi 50010-056	100	10	1" BSP cyl.	Bypass 3,5 bar	No		13522732
Pi 50010-080	100	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522740
Pi 50010-059	100	10	1" BSP cyl.	Bypass 3,5 bar	Optic		13522735
Pi 50010-057	100	10	1" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13522733
Pi 50010-058	100	10	1" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13522734

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.