



DANFOSS Vane Pump VMQ

Characteristics

Mounting flange: SAE-C 2 bolts

Drive shaft: Cylindrical 1.1/4" (31,75 mm) SAE-C

Execution (single/tandem): Single

Type: Vane pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
10	Clockwise	293	SAE 3000 psi 1.1/2"	SAE 3000 psi 1"	708-0002-032	12482799
16	Clockwise	293	SAE 3000 psi 1.1/2"	SAE 3000 psi 1"	708-0004-032	12482800
20	Clockwise	293	SAE 3000 psi 1.1/2"	SAE 3000 psi 1"	708-0143-032	12482801
25	Clockwise	293	SAE 3000 psi 1.1/2"	SAE 3000 psi 1"	708-0012-032	12482802
40	Clockwise	293	SAE 3000 psi 1.1/2"	SAE 3000 psi 1"	708-0025-032	12482804

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.