

DANFOSS Axial piston pump PVQ



Characteristics

Mounting flange: SAE-B 2 bolts

Drive shaft: Cylindrical 3/4" [19,05 mm] SAE-A

Execution (single/tandem): Single

Type: Axial piston pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Pump control	Max. operating pressure bar	Inlet port	Outlet port	Drain port	Code	Article
10,5	Clockwise	Load-Sensing control	210	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341579	1033475
10,5	Clockwise	Pressure control [external]	210	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341584	1033474
10,5	Clockwise	Pressure control	210	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341576	1033473
13,8	Clockwise	Pressure control [external]	140	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341649	1044420
13,8	Clockwise	Pressure control	140	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341644	1044423
21,1	Clockwise	Load-Sensing control	210	1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341555	1033479
21,1	Clockwise	Pressure control		1.1/16-12 UNF female	1.1/16-12 UNF female	9/16-18 UNF female	02-341552	1033477
21,1	Clockwise	Pressure control	210	1,5/16-12 UNF female	1,5/16-12 UNF female	9/16-18 UNF female	02-341561	1044495

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.