



SMC Filter Regulator + Lubricator, series AC10A-40A-A

- Filter Regulator + Lubricator.
- Body size: 10, 20, 30, 40.
- Port Size: M5, 1/8, 1/4, 3/8, 1/2, 3/4.
- Max. operating pressure: 1.0 MPa.
- Attachments.

Characteristics

Series: AC-A

Function: Filter-Regulator-Lubricator

Bowl Material: Polycarbonate

Lockable: No

Operating temperature: -5 / 60 °C

Size	Port thread type	Port Size in	Filtration level µm	With pressure gauge	Drain type	Flow direction	Self-venting	Adjustment range	Article
									24114308
20	BSPP [G]	1/8	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230657
20	BSPP [G]	1/4	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	11884848
40	BSPP [G]	3/4	5	No	Manual	left ? right	Yes	0.05 - 0.7 Mpa	12230689

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.