



NORGREN Electrically operated Excelon P74F soft-start valve

- Assists machine designers in complying with the European Machinery Directive
- Can help existing machinery to comply with PUWER (Provision and Use of Work Equipment Regulations)
- Controlled increase of downstream pressure on start up
- High forward flow capacity
- High flow dump capacity

Characteristics

Series: Excelon

Type: P74F

Housing material: Aluminium

Seal material: Nitrile rubber

Manufacturer ID	Connection	Port Size in	Operating pressure bar	Article
P74F-3GC-PFN	BSPP[G]	3/8		11586308
P74F-4GC-NNN	BSPP[G]	1/2		11586312
P74F-4GC-PFN	BSPP[G]	1/2	3 / 10	11586314
P74F-4GC-PFA	BSPP[G]	1/2		11586313
P74F-6GC-NNN	BSPP[G]	3/4		11586315
P74F-6GC-PFN	BSPP[G]	3/4	3 / 10	11586317

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.