



NORGREN Series 030 manually operated in-line Super X 3/2 valve

- Wide range of operators
- Suitable for multi-directional flow and dual supply applications
- High flow capacity
- Lightweight corrosion resistant materials

Characteristics

Series: Super X

Operation: Manual

Operating temperature: 0 / 70 °C

Material cover: Nylon, glas filled

Fluid: Compressed air

Port thread type	Port Size in	Operating pressure bar	Function	Colour push button	Housing material	Article
BSPP (G)	1/8		3/2			11573768
BSPP (G)	1/8		3/2	Black		11573778
BSPP (G)	1/8		3/2			11573766
BSPP (G)	1/8		3/2	Red		11573776
BSPP (G)	1/8	0 / 10	3/2	Green	Zinc	11573777
BSPP (G)	1/8		3/2			11573814
BSPP (G)	1/8	0 / 10	3/2		PA6	12482898
BSPP (G)	1/8	0 / 10	3/2 Normally closed		Zinc	11573772
BSPP (G)	1/4	0 / 10	3/2		Zinc	11573819
BSPP (G)	1/4	0 / 10	3/2		Zinc	11573825
BSPP (G)	1/4		3/2			11573821
BSPP (G)	1/4		3/2			11573831
BSPP (G)	1/4	0 / 10	3/2 Normally closed		Zinc	11573826
BSPP (G)	1/4	0 / 10	3/2 Normally closed		Zinc	11573828
BSPP (G)	1/4	0 / 10	3/2 Normally closed		Zinc	11573829
BSPP (G)	1/4	0 / 10	3/2 Normally closed		Zinc	11573830
BSPP (G)	1/4	0 / 10	3/2 Normally closed		Zinc	11573827

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.