



AVENTICS 4/2-directional valve Series 840

Characteristics

Series: 840
Operation: Electrical
Type of body: Body Ported
Seal material: NBR

Flow Rate (6 bar - delta p = 1 bar) NI/min	Port Size mm	Operating pressure bar	Maximum operating pressure bar	Function	Pilot supply	Operating voltage	Electrical connection	Protection class	Housing material	Article
200	Ø 6x1	1.5 / 10	10	4/2	Internal	24V DC	Plug EN 175301-803 type C	IP65	POM	12993166
200	Ø 6x1	1.8 / 10	10	4/2	Internal	24V DC	Plug EN 175301-803 type C	IP65	POM	24105061
200	Ø 6x1	1.8 / 10	10	4/2	Internal	24V DC	Plug EN 175301-803 type C	IP65	POM	12704890
200	Ø 6x1	1.5 / 10	10	4/2	Internal	24V DC	Plug EN 175301-803 type C	IP65	POM	11304177
200	Ø 6x1	1.5 / 10	10	4/2	Internal	24V DC	Plug EN 175301-803 type C	IP65	POM	24105060

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.