



AVENTICS 5/2-directional valve Series 740

Characteristics

Series: 740
Operation: Pneumatic
Type of body: Body Ported
Operating temperature: -25 / 50 °C
Seal material: NBR

Flow Rate (6 bar - delta p = 1 bar) NI/min	Port Size mm	Operating pressure bar	Maximum operating pressure bar	Function	Pilot supply	Operating voltage	Electrical connection	Protection class	Housing material	Article
700	Ø 8x1	1.5 / 10	10	5/2	Internal		Plug EN 175301-803 type A	IP65	PAA	24105054
700	Ø 8x1	1.5 / 10	10	5/2	Internal		Plug EN 175301-803 type A	IP65	PAA	11304173
700	Ø 8x1	1.5 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	PAA	23575494
700	Ø 8x1	1.5 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	PAA	24145379
1100	Ø 10x1	1.5 / 10	10	5/2	Internal		Plug EN 175301-803 type A	IP65	PAA	12507833
950	Ø 10x1	1.5 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	PAA	24105055
950	Ø 10x1	1.5 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	PAA	12647953
950	Ø 10x1	1.5 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	PAA	12647954

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.