



TELEMECANIQUE Connector, OsiSense, XZ

Description	Article
Connector Elbowed female DIN 43650 A 4 pins PG11 16A 250VAC	TQXZCC43FCP40B
Connector Elbowed female M12 4 pins PG7 3A 125VAC 150VDC	TQXZCC12FCP40B
Connector Elbowed female M12 4 pins PG7 3A 125VAC 150VDC	TQXZCC12FCM40B
Connector Elbowed male M12 4 pins PG7 3A 125VAC 150 VDC	TQXZCC12MCM40B
Connector Straight female 1/2 20UNF 3 pins PG7 4A 250VAC	TQXZCC20FDM30B
Connector Straight female M12 4 pins PG7 3A 125VAC 150 VDC	TQXZCC12FDM40B
Connector Straight female M12 4 pins PG7 3A 125VAC 150 VDC	TQXZCC12FDP40B
Connector Straight female M12 5 pins PG7 3A 30VAC 36 VDC	TQXZCC12FDM50B
Connector Straight male 1/2 20 UNF 3 pins PG7 4A 250VAC	TQXZCC20MDM30B
Connector Straight male M12 4 pins PG7 3A 125VAC 150 VDC	TQXZCC12MDM40B
Connector Straight male M12 4 pins PG7 3A 30VAC 36 VDC	TQXZCC12MDM50B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.