



ASCO Solenoid valve 2/2 Type: 32300 series 210 brass internal thread

Characteristics

Series: 210
Type: 32300
Function: Normally closed (NC)
Actuation: Pilot operated hung diaphragm
Electrical connection: Plug EN 175301-803 type A
Housing material: Brass
Material coil housing: Epoxy
Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Explosion-proof: No
SIL certified: No

Application

- In systems with a small differential pressure or as a drain from a pressureless tank. Neutral gases.
- Neutral liquids.
- Hydraulic oils.
- With FKM/FPM seals suitable for biofuels

Technical Information

- Robust construction.

Maximum pressure difference table							
Size	dP ^{min}	dP ^{max} Water		dP ^{max} Gas		dP ^{max} Oil	
		V AC	V DC	V AC	V DC	V AC	V DC
3/8"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
1/2"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
3/4"	0 bar	9 bar	3 bar	9 bar	3 bar	-	-
1"	0 bar	9 bar	6 bar	9 bar	6 bar	9 bar	6 bar
1.1/4"	0 bar	9 bar	6 bar	9 bar	6 bar	9 bar	6 bar
1.1/2"	0 bar	9 bar	5 bar	9 bar	5 bar	9 bar	5 bar

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.