

## ASCO Solenoid valve 2/2 Type: 32205 series 210 brass internal thread

## **Characteristics**

Series: 210 **Type:** 32205

Function: Normally closed (NC) **Actuation:** Indirect-acting

Electrical connection: Plug EN 175301-803 type A

Housing material: Brass Material coil housing: Epoxy Material shorting ring: Copper

Working time: 100 %

Level of protection (IP value): IP65

Explosion-proof: No SIL certified: No

## **Application**

• Water.

• Hydraulic oil. • Neutral fluids.

• Neutrale gases.

Maximum pressure difference table							
	dP <sup>max</sup> Water		dP <sup>max</sup> Gas		dP <sup>max</sup> Oil		
Size	dP <sup>min</sup>	V AC	V DC	V AC	V DC	V AC	V DC
3/8"	0.35 bar	9 bar	14 bar	7 bar	10 bar	7 bar	10 bar
1/2"	0.35 bar	9 bar	14 bar	7 bar	10 bar	7 bar	10 bar
3/4"	0.35 bar	7 bar	9 bar	6 bar	9 bar	6 bar	9 bar

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR10370167023415834\_EN\_20.04.2024 Page 1/1