



ASCO Solenoid valve 2/2 Type: 32400 serie 210 brass internal thread

Characteristics

Series: 210
Type: 32400
Function: Normally open (NO)
Actuation: Pilot operated hung diaphragm
Electrical connection: Plug EN 175301-803 type A
Housing material: Brass
Material coil housing: Steel epoxy coating
Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP66/IP67
Explosion-proof: Yes
SIL certified: No

Application

- Especially in systems where the valve has to open when no voltage is present. Neutral gases.
- Neutral liquids.
- Hydraulic Oils.
- With FKM/FPM sealing and membrane suitable for biofuels.

Maximum pressure difference table

Size	dP ^{min}	dP ^{max} Water		dP ^{max} Gas		dP ^{max} Oil	
		V AC	V DC	V AC	V DC	V AC	V DC
3/8"	0 bar	9 bar	9 bar	9 bar	9 bar	9 bar	5 bar
1/2"	0 bar	9 bar	9 bar	9 bar	9 bar	9 bar	5 bar
3/4"	0 bar	9 bar	9 bar	9 bar	9 bar	9 bar	5 bar
1"	0 bar	9 bar	-	9 bar	-	9 bar	-
1.1/4"	0 bar	9 bar	-	9 bar	-	9 bar	-

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.