



## FLEXION Process gauge black-painted steel with BSPT(R) bottom entry

### Characteristics

**Type:** PG

**Connection location:** Bottom side

**Cabinet material:** Black Painted Steel

**Process connection material:** Brass

**Window material:** Polycarbonate

Measuring range	Pressure unit	Cabinet diameter mm	Connection	Size of process connection	Article
-1 / 0	bar/psi	63	External thread (BSPP)	1/4	PG63-0/-1-BE-FX
0 / 20	bar/psi	50	External thread (BSPP)	1/8	PG50-20-BE-FX
0 / 16	bar/psi	50	External thread (BSPP)	1/8	PG50-16-BE-FX
0 / 1	bar/psi	50	External thread (BSPP)	1/8	PG50-0/-1-BE-FX
0 / 6	bar/psi	50	External thread (BSPP)	1/8	PG50-06-BE-FX
0 / 2	bar/psi	50	External thread (BSPP)	1/8	PG50-02-BE-FX
0 / 10	bar/psi	50	External thread (BSPP)	1/8	PG50-10-BE-FX
0 / 2	bar/psi	63	External thread (BSPP)	1/4	PG63-02-BE-FX
0 / 20	bar/psi	63	External thread (BSPP)	1/4	PG63-20-BE-FX
0 / 16	bar/psi	63	External thread (BSPP)	1/4	PG63-16-BE-FX
0 / 6	bar/psi	63	External thread (BSPP)	1/4	PG63-06-BE-FX
1 / 10	bar/psi	63	External thread (BSPP)	1/4	PG63-10-BE-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.