

FLEXION Process gauge stainless steel AISI 316L with BSPP (G) bottom entry

Characteristics

Series: PG Type: PG Process connection: External thread Process connection material: Stainless steel 316L Window material: Safety glass

Cabinet diameter	Measuring range	Pressure unit	Connection location	Size process connection	Cabinet material	Article
mm						
100	-1 / 0	bar/psi	Below	1/2" BSPP[G]	Stainless steel 316L	PG100-SS-0/-1-BE-FX
100	0 / 2	bar/psi	Below	1/2" BSPP[G]	Stainless steel 316L	PG100-SS-02-BE-FX
100	0 / 6	bar/psi	Below	1/2" BSPP(G)	Stainless steel 316L	PG100-SS-06-BE-FX
100	0 / 10	bar/psi	Below	1/2" BSPP(G)	Stainless steel 316L	PG100-SS-10-BE-FX

PR10370167023436785_EN_23.04.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1



T

