



ECON® Check valve Type: 102 Cast iron Flange PN16

Cast iron angle pattern check valve, piston type, bronze internals with bolted cover and flanged ends, pressure class PN16.

Characteristics

Type: 102

Norm: EN (DIN)

Construction type: Angle Pattern

Housing material: Cast iron

Material quality: EN-JL1040

Surface protection: Standard manufacturers coating

Connection: Flange

Flange finish: Raised face

Face to Face norm: EN 558, Series 8

With spring: Yes

Spring material: CuSn6

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 225 °C

Maximum pressure difference at 20 °C: 16 bar

Application


- General Industry.
- On board ships (maritime).
- Neutral liquids.
- Seawater, hot or cold water, oil, etc.
- Suitable for horizontal and vertical (rising flow) mounting.

Technical Information

- Design: EN 12334.
- Testing: EN 12266-1 rate C.

Options

- Available in straight pattern; type 101.
- Available with stainless steel internals; type 78.



DN	A	L1	H	Weight	Kv-value	Min. opening pressure
mm	mm	mm	mm	[kg]	[m3/hr]	[bar]
15	95	90	56	2,1	5,6	0,05 - 0,1
20	105	95	56	2,7	7,2	0,05 - 0,1
25	115	100	67	3,8	13,1	0,05 - 0,1
32	140	105	76	5,5	17,5	0,05 - 0,1
40	150	115	89	7,4	30	0,05 - 0,1
50	165	125	96	9,5	40,5	0,05 - 0,1
65	185	145	104	15	79	0,05 - 0,1
80	200	155	124	20	115	0,05 - 0,1
100	220	175	161	29	181	0,05 - 0,1
125	250	200	174	41	225	0,05 - 0,1
150	285	225	197	66	364	0,05 - 0,1
200	340	275	248	111	690	0,05 - 0,1
250	405	325	333	196	1010	0,05 - 0,1
300	460	375	375	302	--	0,05 - 0,1

	-10/120°C	150°C	180°C	200°C	225°C	
PN16	16	14,4	13,4	12,8	12	[bar]

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Face to Face length	Valve shape	Kv value	Sealing	Material disc	Material cover	Material cover gasket	Material shaft	Article
		mm		m³/h						
DN50	PN16	125	Flap	51	Bronze	CC480K	EN-JL1040	Graphite	CC480K	EC001020050-GBZP

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.