



ECON® Check valve Type: 1430 Bronze Internal thread (NPT) PN16


Characteristics

- Type:** 1430
- Norm:** ASME
- Construction type:** Straight
- Housing material:** Bronze
- Material quality:** CC491K (RG5)
- Connection:** Internal thread (NPT)
- Face to Face norm:** Manufacturer standard

Maximum medium temperature (continuous): 200 °C
Maximum pressure difference at 20 °C: 16 bar

Application

- Recommended in: Petrochemical and Refining



DN ["]	L mm	H mm
½	60	40
¾	70	49
1	80	57
1 ¼	95	59
1 ½	105	68
2	130	76

Press.- and temperature range		
16 bar - 120°C		12 bar - 200°C

Nominal inner diameter	Pressure rating	Face to Face length mm	Valve shape	Sealing	Material disc	Material cover	Material cover gasket	Material jointed arm	Minimum medium temperature (continuous) °C	Article
1" [25]	PN16	80	Swing type	Brass	Brass	Brass	Fiber Gasket	Brass	-10	EC014300001-BB33
2" [50]	PN16	130	Swing type	Brass	Brass	Brass	Fiber Gasket	Brass	-10	EC014300002-BB33

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.