



SMC Speed Controller, One-touch Fitting, Flat Head Screwdriver Adjusting series AS*1F-D

- Flat head screw driver adjustable speed controller
- with one-touch fittings
- Flow rate can be adjusted with a flat head screw driver
- Prevents inadvertent manual operation
- Elbow style
- Meter-in or meter out control
- Body sizes: M5, 1/8, 1/4, 3/8, 1/2
- Various port sizes in both inch and metric

Characteristics

Series: AS-D

Execution: Flow/check valve

Mounting: Threaded

Material housing: PBT/Nickel-plated brass

Seal material: NBR

Operating pressure: 1 / 10 bar

Temperature range: -5 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010

Port thread type	Pneumatic connection 1	Article
BSPT (R)	1/4	AS2201F-02-08SD
BSPT (R)	1/8	AS2201F-01-08SD
BSPT (R)	1/8	AS2201F-01-06SD
BSPT (R)	1/8	AS2201F-01-04SD
BSPT (R)	3/8	AS3201F-03-08SD
External thread (Metric)	M 5	AS1201F-M5-04D
External thread (Metric)	M 5	AS1201F-M5-06D

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.