



FLEXION Allen key plug with o-ring nickel plated brass male BSPP(G) and metric

Characteristics

- Type:** PLG-B-HEX-OR
- Ambient temperature:** -20 / 100 °C
- Operation temperature:** -20 / 100 °C
- Operating pressure:** -0.95 / 60 bar
- Maximum operating pressure [Bar]:** 60 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Article
PLG-B-HEX-OR-M5-FX	Brass, Nickel-plated	External thread (M)	M 5	PLG-B-HEX-OR-M5-FX
PLG-B-HEX-OR-1/2-FX	Brass, Nickel-plated	External thread BSPP (G)	1/2	PLG-B-HEX-OR-1/2-FX
PLG-B-HEX-OR-1/4-FX	Brass, Nickel-plated	External thread BSPP (G)	1/4	PLG-B-HEX-OR-1/4-FX
PLG-B-HEX-OR-1/8-FX	Brass, Nickel-plated	External thread BSPP (G)	1/8	PLG-B-HEX-OR-1/8-FX
PLG-B-HEX-OR-3/8-FX	Brass, Nickel-plated	External thread BSPP (G)	3/8	PLG-B-HEX-OR-3/8-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.