



FLEXION Bulkhead adaptor nickel plated brass female BSPP (G) and metric

Characteristics

- Type: BULK-B-FF
- Ambient temperature: -20 / 100 °C
- Operation temperature: -20 / 100 °C
- Operating pressure: -0.95 / 60 bar
- Maximum operating pressure [Bar]: 60 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
BULK-B-FF1/2-M28X1.5-FX	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	Internal thread (M)	M 28x1.5	BULK-B-FF1/2-M28X1.5-FX
BULK-B-FF1/4-M20X1.5-FX	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	Internal thread (M)	M 20x1.5	BULK-B-FF1/4-M20X1.5-FX
BULK-B-FF1/8-M16X1.5-FX	Brass, Nickel-plated	Internal thread BSPP (G)	1/8	Internal thread (M)	M 16x1.5	BULK-B-FF1/8-M16X1.5-FX
BULK-B-FF3/8-M26X1.5-FX	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	Internal thread (M)	M 26x1.5	BULK-B-FF3/8-M26X1.5-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.