

ECON® Pressure gauge valve Type 861 brass internal/external thread



Characteristics

Type: 861


Housing material: Brass

Operation: Hand wheel

Material tension socket: Steel

Material swivel nut: Steel

Type 1



Process connection	Size process connection	Connection instrument side	Size instrument connection	Inspection connection	Pressure rating	Maximum pressure at 20 °C bar	Maximum medium temperature (continuous) °C	Primary spindle seal material	Spindle material	Article
External thread	1/2" BSPP(G)	Tension socket	1/2" BSPP(G)	M20x1.5	PN250	250	120	PTFE	1.4101	EC0086101/2-DABH
External thread	1/2" BSPP(G)	Tension socket	1/2" BSPP(G)	None	PN250	250	120	PTFE	1.4104	EC0861M01/2-MAAAAAO
External thread	1/4" BSPP(G)	Tension socket	1/4" BSPP(G)	None	PN125	125	120	PTFE	1.4104	EC0086101/2-DABL
External thread	1/4" BSPP(G)	Tension socket	1/4" BSPP(G)	None	PN125	125	120	PTFE	1.4104	EC0086101/4R-ABL

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.