


SMITH Globe valve Type: 1741S Steel Socket weld Class 800



Characteristics

Type: 1741S

Norm: ASME

Construction type: Straight

Housing material: Steel

Connection: Socket weld

Standard welding connection: ASME B16.11

Stem seal type: Gland seal

Primary spindle seal material: Graphite

DN ["]	L mm	H (Open) mm	M mm	Weight [kg]
½	83	160	102	1.7
¾	89	165	102	2.2
1	114	173	102	2.8
1 ½	159	206	118	5.6
2	184	252	168	10.2

-31/38 °C	93 °C	149 °C	204 °C	260 °C	316 °C	343 °C	371 °C	399 °C	427 °C	454 °C	482 °C	510 °C	538 °C
bar	bar	bar	bar	bar	bar	bar	bar	bar	bar	bar	bar	bar	bar
136	124,8	120,4	116,4	110,9	104,4	101,1	97,4	93,2	75,7	58,6	42,3	25,2	15,6
ASTM A 105N is not recommended for prolonged use over 426°													
Check the data above to ASME B16.34 (latest revision)													

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.