



ASCO Solenoid valve 2/2 fig. 32000 series 256B brass normally closed

Characteristics

Series: 256

Type: 32000

Function: Normally closed (NC)

Actuation: Direct-acting


Electrical connection: Plug EN 175301-803 type B

Housing material: Brass

Material shorting ring: Copper

Working time: 100 %

Level of protection (IP value): IP65



Maximum allowable differential pressure table

Process connection	Coil type	Orifice	dP Min.	dP Max. air/gas		dP Max. water		dP Max. light oil	
				(=DC)	(~AC)	(=DC)	(~AC)	(=DC)	(~AC)
BSPP		mm	bar	bar	bar	bar	bar	bar	bar
1/8"	SPC22 35008	1.2	0	20	28	20	28	20	28
1/8" - 1/4"	SPC22 35008	1.6	0	12	20	12	20	12	20
1/8"	SPC22 35008	2	0	6	15	6	15	6	15
1/8" - 1/4"	SPC22 35008	2.4	0	4	12	4	12	4	12
1/4"	SPC 35011	1.6	0	15	20	15	20	15	20
1/4"	SPC 35011	2.4	0	8	15	8	15	8	15
1/4" *	SPC 35011	4	0	2	5	2	5	2	5
1/4" *	SPC 35011	5	0	1	3	1	3	1	3

* Without manual emergency control

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.