

ASCO Solenoid valve 2/2 Type: 32000 series 256B brass normally closed

Characteristics

Series: 256 Type: 32000 Function: Normally closed (NC) Actuation: Direct-acting Electrical connection: Plug EN 175301-803 type B Housing material: Brass Material shorting ring: Copper Working time: 100 % Level of protection (IP value): IP65

Application

- Water.
- Neutral gases.
- Hydraulic oil.

Technical Information

- Standard FPM seal.
- Conversion from AC to DC coil possible.

Maximum allowable differential pressure table									
Process connection	Coil type	Orifice	dP Min.	dP Max. air/gas		dP Max. water		dP Max. light oil	
				(=DC)	(~AC)	(=DC)	(~AC)	(=DC)	[~AC]
BSPP		mm	bar	bar	bar	bar	bar	bar	bar
1/8"	SPC22 35008	1.2	0	20	28	20	28	20	28
1/8" - 1/4"	SPC22 35008	1.6	0	12	20	12	20	12	20
1/8"	SPC22 35008	2	0	6	15	6	15	6	15
1/8" - 1/4"	SPC22 35008	2.4	0	4	12	4	12	4	12
1/4"	SPC 35011	1.6	0	15	20	15	20	15	20
1/4"	SPC 35011	2.4	0	8	15	8	15	8	15
1/4" *	SPC 35011	4	0	2	5	2	5	2	5
1/4" *	SPC 35011	5	0	1	3	1	3	1	3
* Without manual emergency control									

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

T

