

Circular saw blade HSS-E type 2668

stoom.

Design: Made of cobalt-alloyed high-speed steel, steam-tempered surface, suitable for all common machine types.

Types of tooth:

Blade diameter	Material	Thickness	Hole diameter	Number of teeth	Article
mm		mm	mm		
225	HSS-co	2	32	120	W90A-26680001
225	HSS-co	2	32	180	W90A-26680003
250	HSS-co	2	32	128	W90A-26680005
250	HSS-co	2	32	200	W90A-26680007
275	HSS-co	2.5	40	110	W90A-26680013
275	HSS-co	2.5	40	144	W90A-26680015
275	HSS-co	2.5	40	180	W90A-26680017
275	HSS-co	2.5	40	220	W90A-26680019
300	HSS-co	2.5	32	160	W90A-26680023
300	HSS-co	2.5	32	240	W90A-26680025
315	HSS-co	2.5	32	160	W90A-26680035
315	HSS-co	2.5	32	250	W90A-26680037
315	HSS-co	3	40	160	W90A-26680041
315	HSS-co	3	40	250	W90A-26680043
350	HSS-co	3	40	140	W90A-26680047
350	HSS-co	3	40	180	W90A-26680049

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR1443594106651_EN_19.05.2024