

## WIKUS Bandsaw type MARATHON® M42



Design: Wear-resistant saw teeth made of HSS in M42 quality combined with very hard tips.  
WIKUS MARATHON® M42: Tooth pitch up to 578 teeth per inch, rake angle positive.

### Application:

For sawing all steels up to 45 HRC, for layer and bundle cutting of larger workpiece dimensions, for large profiles and solid materials and for non-ferrous metals.

### Characteristics

**Type:** Band saw blade

| Length | Number of teeth per inch | Thickness | Height | Material | Article       |
|--------|--------------------------|-----------|--------|----------|---------------|
| mm     |                          | mm        | mm     |          |               |
| 2450   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610270 |
| 2450   | 5/8                      | 0.9       | 27     | Bimetal  | W90A-27610275 |
| 2700   | 5/8                      | 0.9       | 27     | Bimetal  | W90A-27610085 |
| 2750   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610097 |
| 2835   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610112 |
| 2950   | 3/4                      | 0.9       | 27     | Bimetal  | W90A-27610127 |
| 2950   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610130 |
| 3150   | 3/4                      | 0.9       | 27     | Bimetal  | W90A-27610145 |
| 3150   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610148 |
| 3320   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610163 |
| 3320   | 6/10                     | 0.9       | 27     | Bimetal  | W90A-27610169 |
| 3660   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610178 |
| 3830   | 3/4                      | 0.9       | 27     | Bimetal  | W90A-27610193 |
| 3830   | 4/6                      | 0.9       | 27     | Bimetal  | W90A-27610196 |
| 4115   | 2/3                      | 1.3       | 41     | Bimetal  | W90A-27610238 |
| 4115   | 3/4                      | 1.3       | 41     | Bimetal  | W90A-27610241 |
| 4115   | 4/6                      | 1.3       | 41     | Bimetal  | W90A-27610244 |
| 4200   | 3/4                      | 1.1       | 34     | Bimetal  | W90A-27610214 |
| 4200   | 4/6                      | 1.1       | 34     | Bimetal  | W90A-27610217 |
| 4400   | 2/3                      | 1.1       | 34     | Bimetal  | W90A-27610220 |
| 4400   | 3/4                      | 1.1       | 34     | Bimetal  | W90A-27610223 |
| 4400   | 4/6                      | 1.1       | 34     | Bimetal  | W90A-27610226 |
| 4570   | 3/4                      | 1.1       | 34     | Bimetal  | W90A-27610285 |
| 4570   | 4/6                      | 1.1       | 34     | Bimetal  | W90A-27610290 |
| 4640   | 2/3                      | 1.3       | 41     | Bimetal  | W90A-27610247 |
| 4640   | 3/4                      | 1.3       | 41     | Bimetal  | W90A-27610250 |
| 4640   | 3/4                      | 1.1       | 34     | Bimetal  | W90A-27610232 |
| 4640   | 4/6                      | 1.3       | 41     | Bimetal  | W90A-27610253 |
| 5334   | 3/4                      | 1.3       | 41     | Bimetal  | W90A-27610259 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.