



## WIKUS Bandsaw type Proflex® M42

HSS  
Bimetaal

Design: Wear-resistant saw teeth made of HSS in M42 quality combined with very hard tips.

WIKUS PROFLEX® M42 [68-69 HRC]: Tooth pitch up to 8?11 teethper inch, rake angle positive, with special tooth geometry.

Application: For the sawing of profiles and beams of various dimensions and for sawing work susceptible to vibrations. For single and bundle cutting.

### Characteristics

**Type:** Band saw blade

| Length<br>mm | Number of teeth per<br>inch | Thickness<br>mm | Height<br>mm | Material | Article       |
|--------------|-----------------------------|-----------------|--------------|----------|---------------|
| 2450         | 3/4                         | 0.9             | 27           | Bimetal  | W90A-27660001 |
| 2450         | 5/7                         | 0.9             | 27           | Bimetal  | W90A-27660004 |
| 2450         | 8/11                        | 0.9             | 27           | Bimetal  | W90A-27660007 |
| 2750         | 3/4                         | 0.9             | 27           | Bimetal  | W90A-27660010 |
| 2750         | 5/7                         | 0.9             | 27           | Bimetal  | W90A-27660013 |
| 2750         | 8/11                        | 0.9             | 27           | Bimetal  | W90A-27660016 |
| 3150         | 3/4                         | 0.9             | 27           | Bimetal  | W90A-27660019 |
| 3150         | 5/7                         | 0.9             | 27           | Bimetal  | W90A-27660022 |
| 3150         | 8/11                        | 0.9             | 27           | Bimetal  | W90A-27660025 |
| 3320         | 3/4                         | 0.9             | 27           | Bimetal  | W90A-27660028 |
| 3320         | 5/7                         | 0.9             | 27           | Bimetal  | W90A-27660031 |
| 3320         | 8/11                        | 0.9             | 27           | Bimetal  | W90A-27660034 |
| 3660         | 3/4                         | 0.9             | 27           | Bimetal  | W90A-27660037 |
| 3660         | 5/7                         | 0.9             | 27           | Bimetal  | W90A-27660040 |
| 3660         | 8/11                        | 0.9             | 27           | Bimetal  | W90A-27660043 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.