

## FORMAT Aluminium workplace caliper with points type 4061



DIN 862	RVS	IP 65	Absolut-System	Certificaat	RS232	USB
---------	-----	-------	----------------	-------------	-------	-----

**Design:** Made of stainless steel, hardened, measuring faces precision ground, with locking screw, digit height of LCD 8.5 mm for 300 mm and 12.5 mm over 500 mm measuring range, inductive measurement system, with variable data output RS 232, USB and Digimatic [DATA Variable]. Supplied with battery CR 2032, 3 V, in a wooden box.

**Function:** On and automatic off switch, mm/inch switching, automatic switching by means of slider movement, key lock set for zero position, re-zeroing after switching deleted [absolute system], reset [zeroing] possible at each position,  $\pm$  pre-set function [setting a numerical value].

**Application:** For inside and outside measurements.

**Note:** Replacement battery [Order No. 4027 2032].

Data cable USB [Order No. 4025 0003].

Data cable Digimatic [Order No. 4025 0004].

Data cable RS 232 available on request.

Measuring range mm	Digital indication	Article
0 / 300	Yes	W90A-40610301
0 / 500	Yes	W90A-40610501
0 / 1000	Yes	W90A-40611001

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.