




VSM Fibre abrasive disc corundum for stainless steel- and aluminiumworking type 8763

Design: Resin-bonded aluminium oxide grain [A] on tear-proof, thick, vulcanised fibre backing material uniform and slightly loose. Excellent grit friction, long life, minimal pressure and good flexibility. An active additive in the coating slows disc-clogging during use on soft metals (aluminium, stainless steel, etc.). In addition, the coating acts as a coolant during grinding. With centre hole (standard bore 22.23 mm) and cross slots.

Application: Special product for hard machining, steel alloys and non-ferrous metals with angle and disc grinders as well as abrasive heads on flexible shanks. For all angle grinders with backing pads of max. 80 m/s peripheral speed. Ideal for working with containers, cast parts, body parts etc.

Note: Rubber backing pad see [Order no. 8250].

Description	Article
Fiber abrasive disc top 115mm K120	W90A-87630120
Fiber abrasive disc top 115mm K60	W90A-87630060
Fibre grinding wheel TOP SIZE 115mm K80	W90A-87630080

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.