

HAZET Torque wrench SYSTEM 6000 CT with signal button type 6267



Design: Robust and resistant, hard chrome plated tubular steel construction, ergonomic handle with collar, which reduces slipping-off and injury. Setting the desired torque value quickly and safely by turning the handle. Due to the integrated reversible ratchet function the controlled clockwise tightening is guaranteed. Tactile and acoustic trigger signals. High accuracy due to fine scale division. Delivery includes test certificate DIN EN ISO 6789.

Application: For controlled screw tightening in the corresponding torque range for all industrial manufacturing areas.

Design: Robust and resistant, hard chrome plated tubular steel construction, ergonomic handle with collar, which reduces slipping-off and injury. Setting the desired torque value quickly and safely by turning the handle. Due to the integrated reversible ratchet function the controlled clockwise tightening is guaranteed. Tactile and acoustic trigger signals. High accuracy due to fine scale division. Delivery in plastic box, includes test certificate DIN EN ISO 6789.

Application: For controlled screw tightening in the corresponding torque range for all industrial manufacturing areas.

Connection size	Tightening moment Nm	Total length mm	Article
1/2	20 / 120	435	W90A-62670030
1/2	40 / 200	543	W90A-62670035
1/2	60 / 320	659	W90A-62670040
3/8	20 / 120	389	W90A-62670025

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.