


FLEXION Manifold aluminium single sided BSPP(G)



Characteristics

Type: MFLD-AL

Material: Anodised aluminium

Maximum operating pressure [Bar]: 12 bar

Operating temperature: -40 to +150 °C

Shape	Port thread type	Port thread size in	Supply thread type	Supply thread size in	Number of outlets	Article
Manifold	Internal thread BSPP [G]	1/8	Internal thread BSPP [G]	1/4	3	MFLD-AL-1/4-1/8-3-FX
Manifold	Internal thread BSPP [G]	1/8	Internal thread BSPP [G]	1/4	4	MFLD-AL-1/4-1/8-4-FX
Manifold	Internal thread BSPP [G]	1/8	Internal thread BSPP [G]	1/4	2	MFLD-AL-1/4-1/8-2-FX
Manifold	Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	3/8	4	MFLD-AL-3/8-1/4-4-FX
Manifold	Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	3/8	2	MFLD-AL-3/8-1/4-2-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.