



ASCO Solenoid valve 2/2 fig. 32009 series 262 stainless steel internal thread

Characteristics

Series: 262K

Type: 32009

Function: Normally closed [NC]

Actuation: Direct-acting

Electrical connection: Plug EN 175301-803 type A

Housing material: Stainless steel

Material coil housing: Epoxy

Material shorting ring: Silver

Working time: 100 %

Level of protection (IP value): IP65

Explosion-proof: No

SIL certified: No

Conn. ["]	Coil type	Power	A [mm]	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	Weight [kg]	
1/8	SPC	35350	~ 30 / 16 VA, 8,1 Watt	91	51	30	30	43	62	71	88	18	15	0,3
1/8	SPC	35353	= 10,6 Watt	91	51	30	30	43	62	71	88	18	15	0,3
1/4	SPC	35350	~ 30 / 16 VA, 8,1 Watt	91	51	30	40	43	65	75	92	22	22	0,42
1/4	SPC	35351	~ 45 / 20 VA, 11,1 Watt	91	51	30	40	43	65	75	92	22	22	0,42
1/4	SPC	35353	= 10,6 Watt	91	51	30	40	43	65	75	92	22	22	0,42
1/4	SPC	35354	= 18,6 Watt	91	51	30	40	43	65	75	92	22	22	0,42
1/4	SPC	35360	~ 50 / 25 VA, 10,1 Watt	95	57	33	40	50	69	78	96	22	22	0,6
1/4	SPC	35361	~ 70 / 40 VA, 17,1 Watt	95	57	33	40	50	69	78	96	22	22	0,6
1/4	SPC	35364	= 11,6 Watt	95	57	33	40	50	69	78	96	22	22	0,6
1/4	SPC	35365	= 22,6 Watt	95	57	33	40	50	69	78	96	22	22	0,6
3/8	SPC	35360	~ 50 / 25 VA, 10,1 Watt	95	57	33	48	50	69	80	107	21	19	0,63
3/8	SPC	35361	~ 70 / 40 VA, 17,1 Watt	95	58	33	48	50	69	80	107	21	19	0,63
3/8	SPC	35364	= 11,6 Watt	95	57	33	48	50	69	80	107	21	19	0,63

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Conn. ["]	Coil type	Power = 22,6 Watt	A [mm]	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	Weight [kg]
3/8	SPC	35365	95	57	33	48	50	69	80	107	21	19	0,63
1= Two M5 mounting holes, min. 6mm deep													
2= Emergency manual, optional													

Conn. ["]	Orifice [mm]	Coil type [~AC]	dP Min. [=DC]	Max. differential pressure [bar]	Max. differential pressure								
					Air/gas [~AC]	Water [=DC]	Light oil [~AC]		[=DC]				
1/8	2,4	SPC 35350	SPC 35353	0	25	14	22	10	13	10			
1/8	3,2	SPC 35350	SPC 35353	0	12	8	12	6,5	8	6			
1/4	1,2	SPC 35350	SPC 35353	0	51	51	51	41	50	34			
1/4 *	1,2	SPC 35360	SPC 35364	0	103	68	103	66	103	58			
1/4	2,4	SPC 35350	SPC 35353	0	25	14	22	10	11	10			
1/4	2,4	SPC 35360	SPC 35364	0	40	16	28	16	28	15			
1/4	3,2	SPC 35350	SPC 35353	0	12	8	12	6,5	6	5,5			
1/4	3,2	SPC 35360	SPC 35364	0	23	7,5	20	7	14	6,5			
1/4	4	SPC 35360	SPC 35364	0	14	3,5	13	3,5	10	3,5			
1/4	5,6	SPC 35350	SPC 35353	0	3,5	2	3,5	2	2,5	1,9			
1/4	5,6	SPC 35360	SPC 35364	0	6,5	2	6,5	2	6,5	2			
1/4	7,1	SPC 35350	SPC 35353	0	2	1,6	2	1,5	2	1,3			
1/4	7,1	SPC 35360	SPC 35364	0	4	1,5	5	1,5	4	1,3			
3/8	4	SPC 35360	SPC 35364	0	14	3,5	12	3,5	6,5	3			
43680	5,6	SPC 35360	SPC 35364	0	6,5	2	5,5	2	4,5	2			
43680	5,6	SPC 35361	SPC 35365	0	8,5	4	6,5	4	6,5	4			
43680	7,1	SPC 35361	SPC 35365	0	6,5	3	5,5	3	4,5	3			
Medium temperature: -25°C tot 80°C													
Ambient temperature: -25°C tot 55°C													
* Disc seal of UR. Medium temperature: 0°C tot 60°C													

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.