






## FENNER SMSR Gearbox size B

The Fenner Shaft Mounted Speed Reducer (SMSR) offers a rugged and compact design for easy handling and has as standard a large range of bore sizes between 20mm and 190mm, a torque capacity up to 455.000Nm and with the use of a simple belt drive ratios up to 200:1. The Taper-Grip version offers easy removal and fitting

### Characteristics

**Series:** SMSR

**Model:** Reducer



| Model   | Type of gearbox | Size | Rated torque<br>Nm | Gear Ratio | Diameter input<br>shaft<br>mm | Diameter output<br>bore | Article  |
|---------|-----------------|------|--------------------|------------|-------------------------------|-------------------------|----------|
| Reducer | Hollow Bore     | B    | 256                | 5          | 19                            | 30                      | 116B0501 |
| Reducer | Hollow Bore     | B    | 256                | 5          | 19                            | 40                      | 116B0502 |
| Reducer | Hollow Bore     | B    | 277                | 13         | 19                            | 30                      | 116B1301 |
| Reducer | Hollow Bore     | B    | 277                | 13         | 19                            | 40                      | 116B1302 |
| Reducer | Hollow Bore     | B    | 277                | 20         | 19                            | 30                      | 116B2001 |
| Reducer | Hollow Bore     | B    | 277                | 20         | 19                            | 40                      | 116B2002 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.