



FLEXION Quick release safety coupling probe anodised aluminium female BSPP(G)

Characteristics

Type: QRC


Material: Anodised aluminium

Norm: ISO 4414

Temperature range: -20 / 70 °C

Flow Rate [6 bar - delta p = 1 bar]: 1500 NI/min

Maximum operating pressure [Bar]: 12 bar



Size table:

CH	D1	D2	L1	L2
mm		mm	mm	mm
21	1/4	26	9	73.5
21	3/8	26	10	75.5
24	1/2	26	11	77.5

Thread connection	Size of threaded connection (inch)	CH	D1	D2	L1	L2	Article
	in	mm		mm	mm	mm	
Internal thread BSPP [G]	1/4	21	1/4	26	9	73.5	QRC-46-C-1/4F-FX
Internal thread BSPP [G]	3/8	21	3/8	26	10	75.5	QRC-46-C-3/8F-FX
Internal thread BSPP [G]	1/2	24	1/2	26	11	77.5	QRC-46-C-1/2F-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.