



SAREL Insulated enclosure, Thalassa, GRP

Self-extinguishing monobloc enclosure
 Hot pressed moulded glass fibre reinforced polyester
 IP66 protected conforming to EN60529
 Temperature resistance -50 degrees to + 130 degrees
 IK10 rating resistance to external mechanical impact
 Closure device outside sealed zone, ensuring long term IP66 degree of protection
 Integral top and bottom protective canopies for improved protection against water.

Description	Article
Mounting Plate for box Plain Spacial SDB 206X156mm	SANSYPMD2015
Mounting Plate for PLA enclosure Metallic 1000X1000mm	SANSYPMM1010
Wall-Mounting Enclosure Polyester Monobloc IP66 H430xW330xD200mm	SANSYPLM43G
Wall-Mounting Enclosure Polyester Monobloc IP66 H530xW430xD200mm	SANSYPLM54G
Wall-Mounting Enclosure Polyester Monobloc IP66 H647xW436xD250mm	SANSYPLM64G
Wall-Mounting Enclosure Polyester Monobloc IP66 H747xW536xD300mm	SANSYPLM75G
Wall-Mounting Enclosure Polyester Monobloc IP66 H847xW636xD300mm	SANSYPLM86G

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.