



FLEXION Miniature ball valve nickel-plated brass BSPP(G)

Characteristics

- Series:** BV-MINI-FF
- Construction type:** 2-way
- Housing construction:** 1-part
- Housing material:** Brass
- Material quality:** CW617N
- Surface protection:** Chromium-plated
- Maximum operating pressure [Bar]:** 10 bar

Nominal inner diameter	Manual operation	Bore	With locking device	Material ball	Spindle material	Primary spindle seal material	Actuator material	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
1/8" [6]	Handle	Reduced bore		CW614N chromed	CW614N	NBR	Glass-filled nylon, black coloured	-10	90	BV-MINI-FF-1/8-FX
1/4" [8]	Handle	Reduced bore		CW614N chromed	CW614N	NBR	Glass-filled nylon, black coloured	-10	90	BV-MINI-FF-1/4-FX
3/8" [10]	Handle	Reduced bore		CW614N chromed	CW614N	NBR	Glass-filled nylon, black coloured	-10	90	BV-MINI-FF-3/8-FX
1/2" [15]	Handle	Reduced bore		CW614N chromed	CW614N	NBR	Glass-filled nylon, black coloured	-10	90	BV-MINI-FF-1/2-FX
3/4" [20]	Handle	Reduced bore		CW614N chromed	CW614N	NBR	Glass-filled nylon, black coloured	-10	90	BV-MINI-FF-3/4-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.