



FLEXION Full bore handle ball valve nickel plated brass female BSPP(G)

Characteristics

- Series:** BV-FB-FF
- Construction type:** 2-way
- Housing construction:** 2-part
- Housing material:** Brass
- Material quality:** CW617N
- Surface protection:** Chromium-plated
- Tertiary spindle seal material:** PTFE

Nominal inner diameter	Manual operation	Bore	With locking device	Material ball	Spindle material	Primary spindle seal material	Actuator material	Article
1/4" [8]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-1/4-FX
3/8" [10]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-3/8-FX
1/2" [15]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-1/2-FX
3/4" [20]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-3/4-FX
1" [25]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-1-FX
1.1/4" [32]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-1.1/4-FX
1.1/2" [40]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-1.1/2-FX
2" [50]	Handle	Full bore		CW614N chromed	CW614N	PTFE	Steel, galvanized	BV-FB-FF-2-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.