



NORGREN Pneumatically operated Excelon® P72F soft-start valve

- Assists machine designers in complying with the European Machinery Directive
- Can help existing machinery to comply with PUWER (Provision and Use of Work Equipment Regulations)
- Controlled increase of downstream pressure on start up
- High forward flow capacity
- High flow dump facility

Characteristics

Series: Excelon

Type: P72F

Housing material: Zinc

Seal material: Synthetic

Manufacturer ID	Connection	Port Size in	Operating pressure bar	Article
P72F-2GC-PFA	BSPP(G)	1/4	3 / 10	P72F-2GC-PFA
P72F-2GA-NNN	BSPP(G)	1/4	3 / 17	P72F-2GA-NNN
P72F-2GC-PFN	BSPP(G)	1/4	3 / 10	P72F-2GC-PFN
P72F-2GC-NNN	BSPP(G)	1/4	3 / 10	P72F-2GC-NNN
P72F-3GC-PFN	BSPP(G)	3/8	3 / 10	P72F-3GC-PFN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.