



ECON® Diaphragm drum pressure gauge Type 383 steel bottom connection brass

Characteristics

Type: 383

Pressure unit secondary scale: mmwc (mm water column)

Accuracy class: 1.6 %

Pressure gauge attachment: Direct

Connection location: Below

Process connection: External thread

Cabinet material: Steel

Characteristics [2]

Process connection material: Brass

Material dial: Aluminium

Protection class: IP32

Medium temperature: -20 / 60 °C

Ambient temperature: -20 / 60 °C



Size table:

Cabinet diameter	G	a	b	D	D2	SW	Weight
		mm	mm	mm	mm	mm	kg
R63	1/4"	9.5	40	63	62	14	0.23

Cabinet diameter	Measuring range	Pressure unit	Secondary scale division	Size process connection	Window material	Maximum overpressure	Article
mm						mbar	
63	0 / 160	mbar	0 - 1600	1/4" BSPP(G)	Plastic	1600	EC003831H2A1110
63	0 / 250	mbar	0 - 2500	1/4" BSPP(G)	Plastic	2500	EC003831I2A1110

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.