



LOCTITE 6261 Non-slip, floor & deck coating

Non-slip, single-component epoxy floor and deck coating designed for application in areas of heavy pedestrian traffic or light rolling traffic.

LOCTITE® PC 6261™ is a room temperature-cure, non-slip, single-component epoxy floor and deck coating designed for application in areas of heavy pedestrian traffic or light rolling traffic under typical dry service temperatures of -20°F to +140°F [-29°C to +60°C]. It is used for concrete and steel ramps, walkways, locker rooms, loading docks, marine applications, machine rooms, assembly areas and stairs.

Applies quickly and easily

Fire retardant in its cured state

Available in safety yellow, gray or black

Resists gasoline, oil, acids, alkalis and aliphatic solvents

Reduces accidents (slips and falls) in the workplace

Description	Article
6261 Non-slip, floor & deck coating grey	LOC6261-6.36KG
6261 Non-slip, floor & deck coating yellow	LOC6261YL-6.36KG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.