

ECON® Ball valve Type: 7383FS Stainless steel Fire safe Flange Class 150



Characteristics

Type: 7383FS

Norm: ASME

Construction type: 2-way

Housing construction: 1-part

Housing material: Stainless steel

Material quality: ASTM A351 CF8M

Connection: Flange

Flange finish: Raised face

Top flange standard: ISO 5211

Primary spindle seal material: PTFE

Secondary spindle seal material: FPM (FKM)

Tertiary spindle seal material: Graphite

Body seal: SWG 316L/Graphite

Actuator material: ASTM A351 CF8

Minimum medium temperature (continuous): -29 °C

Maximum medium temperature (continuous): 200 °C

Maximum operating pressure [Bar]: 20 bar

Fire safe: Yes

Application

- Industrial applications up to 20 bar.
- Liquid and gaseous media.
- Recommended in: Food & Beverages

Technical Information

- Flanged connection in accordance with ASME B16.5.
- Floating ball.
- Pressure rating Class 150.
- With top flange in accordance with ISO 5211.
- Media temperature: -29/+200°C.
- 1/2" to 3" with lever and locking device.
- 4" with T-bar.

Construction


- One-piece housing construction.
- Design according to ASME B16.34.
- Full bore.
- Equipped with anti-static design between ball and housing.
- Face-to-face dimension according to manufacturer's standard.

Approval

- Fire-safe approval in accordance with ISO 10497 and API 607, seventh edition.
- TA Luft certified in accordance with VDI 2440, section 3.3.1.3.

Options

- Equipped with worm gearbox and pneumatic, electric or hydraulic actuators.
- Position feedback for manually actuated or automated valves.
- Available with seats in TFM4215.



Size table:

DN	d mm	L mm	H mm	M mm	Weight kg
3" [80]	76	120	162	252	14.5

Pressure and temperature range							
DN	Pressure class	-29	50	100	150	200	[°C]
1/2" up to 2"	Class 150	20	19	18	16	14	[bar]
3" and 4"	Class 150	20	19	18	16	11	[bar]

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Bore	With locking device	Material ball	Seat material	Spindle material	Article
3" [80]	Class 150	Manufacturer standard	Handle	F10	Full bore	Yes	ASTM A351 CF8M	TFM 1600	ASTM A276 316	14449835

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.