



WEG 3 Phase motor W22 Cast iron B5T (4P) WIMES

Characteristics

Series: W22 WIMES

Type: B5T

Speed: 1500 rpm

Mounting: B5T

Number of poles: 4

Full load speed: 1491 rpm

Full load torque: 0.84 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE3	0.12	230/400	63	11	140	M0.124FL63C3AIE3W-WEG
IE3	0.18	230/400	71	11	140	M0.184FL63C3AIE3W-WEG
IE3	0.25	230/400	71	14	160	M0.254FL71C3AIE3W-WEG
IE3	0.37	230/400	71	14	160	M0.374FL71C3AIE3W-WEG
IE3	0.55	230/400	80	19	200	M0.554FL80C3AIE3W-WEG
IE3	0.75	230/400	80	19	200	M0.754FL80C3AIE3W-WEG
IE3	1.1	230/400	90S	24	200	M1.14FL90C3AIE3W-WEG
IE3	1.5	230/400	90L	24	200	M1.54FL90C3AIE3W-WEG
IE3	2.2	230/400	100L	28	250	M2.24FL100C3AIE3W-WEG
IE3	3	230/400	100L	28	250	M3.04FL100C3AIE3W-WEG
IE3	4	230/400	112M	28	250	M4.04FL112C3BIE3W-WEG
IE3	5.5	230/400	132S	38	300	M5.54FL132C3BIE3W-WEG
IE3	7.5	230/400	132M	38	300	M7.54FL132C3BIE3W-WEG
IE3	9.2	230/400	L132M/L	38	300	M9.24FL132C3BIE3W-WEG
IE3	11	230/400	160M	42	350	M11.04FL160C3BIE3W-WEG
IE3	15	230/400	160L	42	350	M15.04FL160C3BIE3W-WEG
IE3	18.5	230/400	180M	48	350	M18.54FL180C3BIE3W-WEG
IE3	22	230/400	180L	48	350	M22.04FL180C3BIE3W-WEG
IE3	30	230/400	200L	55	400	M30.04FL200C3BIE3W-WEG
IE3	37	230/400	225S/M	60	450	M37.04FL225C3BIE3W-WEG
IE3	45	230/400	225S/M	60	450	M45.04FL225C3BIE3W-WEG
IE3	55	230/400	250S/M	65	550	M55.04FL250C3BIE3W-WEG
IE3	75	230/400	250S/M	65	550	M75.04FL250C3BIE3W-WEG
IE3	75	230/400	280S/M	75	550	M75.04FL280C3BIE3W-WEG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE3	90	230/400	280S/M	75	550	M90.04FL280C3BIE3W-WEG
IE3	110	230/400	280S/M	75	550	M110.04FL280C3BIE3W-WEG
IE3	132	230/400	315S/M	80	660	M132.04FL315C3BIE3W-WEG
IE3	150	230/400	315S/M	80	660	M150.04FL315C3BIE3W-WEG
IE3	160	230/400	315S/M	80	660	M160.04FL315C3BIE3W-WEG
IE3	185	230/400	315S/M	80	660	M185.04FL315C3BIE3W-WEG
IE3	200	230/400	315L	80	660	M200.04FL315C3BIE3W-WEG
IE3	220	230/400	315L	80	660	M220.04FL315C3BIE3W-WEG
IE3	250	230/400	315L	80	660	M250.04FL315C3BIE3W-WEG
IE3	260	230/400	315L	80	660	M260.04FL315C3BIE3W-WEG
IE3	315	230/400	355M/L	100	800	M315.04FL355C3BIE3W-WEG
IE3	330	230/400	355M/L	100	800	M330.04FL355C3BIE3W-WEG
IE3	355	230/400	355M/L	100	800	M355.04FL355C3BIE3W-WEG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.