



WEG 3 Phase motor W22 Cast iron B3T (6P) WIMES

Characteristics

Series: W22 WIMES
Type: B3T
Speed: 1000 rpm
Mounting: B3T
Number of poles: 6
Full load speed: 994 rpm
Full load torque: 1.24 Nm
Nominal rated frequency: 50 Hz
Material: Cast iron
PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE3	0.12	230/400	63	11	M0.126FT63C3AIE3W-WEG
IE3	0.18	230/400	71	14	M0.186FT71C3AIE3W-WEG
IE3	0.25	230/400	80	19	M0.256FT80C3AIE3W-WEG
IE3	0.37	230/400	80	19	M0.376FT80C3AIE3W-WEG
IE3	0.55	230/400	80	19	M0.556FT80C3AIE3W-WEG
IE3	0.75	230/400	90S	24	M0.756FT90C3AIE3W-WEG
IE3	1.1	230/400	90L	24	M1.16FT90C3AIE3W-WEG
IE3	1.5	230/400	100L	28	M1.56FT100C3AIE3W-WEG
IE3	2.2	230/400	112M	28	M2.26FT112C3BIE3W-WEG
IE3	3	230/400	132S	38	M3.06FT132C3BIE3W-WEG
IE3	4	230/400	132M	38	M4.06FT132C3BIE3W-WEG
IE3	5.5	230/400	132M	38	M5.56FT132C3BIE3W-WEG
IE3	7.5	230/400	160M	42	M7.56FT160C3BIE3W-WEG
IE3	9.2	230/400	160L	42	M9.26FT160C3BIE3W-WEG
IE3	11	230/400	160L	42	M11.06FT160C3BIE3W-WEG
IE3	15	230/400	180L	48	M15.06FT180C3BIE3W-WEG
IE3	18.5	230/400	200L	55	M18.56FT200C3BIE3W-WEG
IE3	22	230/400	200L	55	M22.06FT200C3BIE3W-WEG
IE3	30	230/400	225S/M	60	M30.06FT225C3BIE3W-WEG
IE3	37	230/400	250S/M	65	M37.06FT250C3BIE3W-WEG
IE3	45	230/400	280S/M	75	M45.06FT280C3BIE3W-WEG
IE3	55	230/400	280S/M	75	M55.06FT280C3BIE3W-WEG
IE3	75	230/400	315S/M	80	M75.06FT315C3BIE3W-WEG
IE3	90	230/400	315S/M	80	M90.06FT315C3BIE3W-WEG
IE3	110	230/400	315S/M	80	M110.06FT315C3BIE3W-WEG
IE3	132	230/400	315S/M	80	M132.06FT315C3BIE3W-WEG
IE3	150	230/400	315L	80	M150.06FT315C3BIE3W-WEG
IE3	160	230/400	315L	80	M160.06FT315C3BIE3W-WEG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE3	185	230/400	315L	80	M185.06FT315C3BIE3W-WEG
IE3	200	230/400	355M/L	100	M200.06FT355C3BIE3W-WEG
IE3	220	230/400	355M/L	100	M220.06FT355C3BIE3W-WEG
IE3	250	230/400	355M/L	100	M250.06FT355C3BIE3W-WEG
IE3	260	230/400	355M/L	100	M260.06FT355C3BIE3W-WEG
IE3	280	230/400	355M/L	100	M280.06FT355C3BIE3W-WEG
IE3	300	230/400	355M/L	100	M300.06FT355C3BIE3W-WEG
IE3	315	230/400	355M/L	100	M315.06FT355C3BIE3W-WEG
IE3	355	230/400	355A/B	100	M355.06FT355C3BIE3W-WEG
IE3	370	230/400	355A/B	100	M370.06FT355C3BIE3W-WEG
IE3	400	230/400	355A/B	100	M400.06FT355C3BIE3W-WEG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.