



SKF Pillow block unit Setscrew Locking Series SY..TF/VA

No need for relubrication

All variants are lubricated for the life of the bearing with graphite-based high temperature lubricants.

Simple replacement

The boundary dimensions are the same as those of standard bearings and units.

Operating temperature up to 350°C (660°F)

The internal radial clearance and the lubricant are optimized for operation at high temperatures.

Quick and easy mounting and dismounting

The grub (set) screws in the inner ring enable quick and easy mounting/dismounting.

Protection against solid contamination

Shields and flingers (designation suffix 2F) protect the bearing.

Improved running in

The entire bearing surface is manganese phosphate coated.

No colour flaking

The housing is coated with a high temperature resistant coating.

Characteristics

Series: SY..TF/VA

Housing style: Pillow Block

Bearing type: Ball bearing

Shaft Locking Type: Setscrew Locking

Manufacturer ID	Housing material	Bearing material	Shaft diameter mm	Article
SY 40 TF/VA228	Steel/cast iron	Bearing steel	40	SY40TFVA228-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.