



WEG 3 Phase motor W22 Cast iron B5T (6P)

Characteristics

Series: W22
Type: B5T
Speed: 1000 rpm
Mounting: B5T
Number of poles: 6
Full load speed: 990 rpm
Full load torque: 1.266 Nm
Nominal rated frequency: 50 Hz
Material: Cast iron
PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE3	0.37	230/400	80	19	200	M0.376FL80C3AIE3-WEG
IE3	0.75	230/400	90S	24		M0.756FL90C3AIE3-WEG
IE3	1.1	230/400	90L	24		M1.16FL90C3AIE3-WEG
IE3	1.5	230/400	100L	28	250	M1.56FL100C3AIE3-WEG
IE3	2.2	400/690	112M	28	250	M2.26FL112C3BIE3-WEG
IE3	3	400/690	L132S	38	300	M3.06FL132C3BIE3-WEG
IE3	4	400/690	132M	38	300	M4.06FL132C3BIE3-WEG
IE3	5.5	400/690	132M/L	38	300	M5.56FL132C3BIE3-WEG
IE3	7.5	400/690	160M	42	350	M7.56FL160C3BIE3-WEG
IE3	11	400/690	160L	42		M11.06FL160C3BIE3-WEG
IE3	15	400/690	180L	48		M15.06FL180C3BIE3-WEG
IE3	18.5	400/690	200L	55	400	M18.56FL200C3BIE3-WEG
IE3	22	400/690	200L	55	400	M22.06FL200C3BIE3-WEG
IE3	30	400/690	225S/M	60	450	M30.06FL225C3BIE3-WEG
IE3	37	400/690	250S/M	65	550	M37.06FL250C3BIE3-WEG
IE4	7.5	400/690	160M	42	350	M7.56FL160C3BIE4-WEG
IE4	11	400/690	160L	42	350	M11.06FL160C3BIE4-WEG
IE4	18.5	400/690	200L	55	400	M18.56FL200C3BIE4-WEG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.