

FENNER V-pulley for taper bush section SPA - 2 grooves

Fenner $^{\circ}$ Taper Lock $^{\circ}$ pulleys are manufactured to the DIN 2210. DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL Type: A/SPA/QXPA Number of grooves: 2 Bore type: Tapered bore

Size table:

К	L	М
mm	mm	mm
33	22	
10	25	
3	32	
	32	
1.5	32	1.5
	45	
	45	10
	45	16

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	М	Article
mm				mm	mm	mm	mm	
63	1108	9	Cast iron	12.7	33	22		SPA63X2-FEN
80	1210	6	Cast iron	12.7	10	25		SPA80X2-FEN
85	1210		Cast iron	12.7				SPA85X2-FEN
90	1610	6	Cast iron	12.7	10	25		SPA90X2-FEN
95	1610	6	Cast iron	12.7	10	25		SPA95X2-FEN
100	1610		Cast iron	12.7				SPA100X2-FEN
106	1610	6	Cast iron	12.7	10	25		SPA106X2-FEN
112	1610		Cast iron	12.7				SPA112X2-FEN
118	1610		Cast iron	12.7				SPA118X2-FEN
125	1610		Cast iron	12.7				SPA125X2-FEN
132	2012		Cast iron	12.7				SPA132X2-FEN
140	2012		Cast iron	12.7				SPA140X2-FEN
150	2012	6	Cast iron	12.7	3	32		SPA150X2-FEN
160	2012		Cast iron	12.7				SPA160X2-FEN
170	2012	2	Cast iron	12.7		32		SPA170X2-FEN
180	2012	7	Cast iron	12.7	1.5	32	1.5	SPA180X2-FEN
190	2517	8	Cast iron	12.7		45		SPA190X2-FEN
200	2517		Cast iron	12.7				SPA200X2-FEN
212	2517	8	Cast iron	12.7		45		SPA212X2-FEN
224	2517	8	Cast iron	12.7		45	10	SPA224X2-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

Page 1/2

PR2277168452067840_EN_25.04.2024

V-belt Pulleys | Taper Bush V-belt Pulleys

Pitch circle diameter	Taper Lock	Model	Material	Groove width	К	L	М	Article
mm				mm	mm	mm	mm	
250	2517		Cast iron	12.7				SPA250X2-FEN
280	2517		Cast iron	12.7				SPA280X2-FEN
315	2517	4	Cast iron	12.7		45	10	SPA315X2-FEN
400	2517	4	Cast iron	12.7		45	10	SPA400X2-FEN
500	2517	4	Cast iron	12.7		45	10	SPA500X2-FEN
630	3020	4	Cast iron	12.7		45	16	SPA630X2-FEN

e or e advice.
Page 2/2
PR2277168452067840_EN_25.04.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS