



FENNER V-pulley for taper bush section SPB - 3 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 3

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
	25	37
	32	31
	45	18
1	65	1

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
112	2012	2	Cast iron	16.1		25	37	SPB112X3-FEN
118	2012	2	Cast iron	16.1		25	37	SPB118X3-FEN
125	2012		Cast iron	16.1				SPB125X3-FEN
132	2012	2	Cast iron	16.1		32	31	SPB132X3-FEN
140	2012		Cast iron	16.1				SPB140X3-FEN
150	2517		Cast iron	16.1				SPB150X3-FEN
160	2517		Cast iron	16.1				SPB160X3-FEN
170	2517		Cast iron	16.1				SPB170X3-FEN
180	2517		Cast iron	16.1				SPB180X3-FEN
190	2517		Cast iron	16.1				SPB190X3-FEN
200	2517	7	Cast iron	16.1		45	18	SPB200X3-FEN
212	2517		Cast iron	16.1				SPB212X3-FEN
224	2517		Cast iron	16.1				SPB224X3-FEN
236	2517		Cast iron	16.1				SPB236X3-FEN
250	3020		Cast iron	16.1				SPB250X3-FEN
280	3020		Cast iron	16.1				SPB280X3-FEN
315	3020		Cast iron	16.1				SPB315X3-FEN
355	3020		Cast iron	16.1				SPB355X3-FEN
400	3525	8	Cast iron	16.1	1	65	1	SPB400X3-FEN
450	3525	4	Cast iron	16.1	1	65	1	SPB450X3-FEN
500	3525	4	Cast iron	16.1	1	65	1	SPB500X3-FEN
560	3525	4	Cast iron	16.1	1	65	1	SPB560X3-FEN
630	3525	4	Cast iron	16.1	1	65	1	SPB630X3-FEN
800	3525	4	Cast iron	16.1	1	65	1	SPB800X3-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.