



FENNER V-pulley for taper bush section SPC - 4 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 4

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
23	65	23
17.5	76	17.5
4.5	102	4.5

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
200	3020		Cast iron	22				SPC200X4-FEN
212	3020		Cast iron	22				SPC212X4-FEN
224	3525	3	Cast iron	22	23	65	23	SPC224X4-FEN
236	3525	3	Cast iron	22	23	65	23	SPC236X4-FEN
250	3525	3	Cast iron	22	23	65	23	SPC250X4-FEN
265	3525	3	Cast iron	22	23	65	23	SPC265X4-FEN
280	3525	3	Cast iron	22	23	65	23	SPC280X4-FEN
300	3525	7	Cast iron	22	23	65	23	SPC300X4-FEN
315	3525	7	Cast iron	22	23	65	23	SPC315X4-FEN
335	3525	7	Cast iron	22	23	65	23	SPC335X4-FEN
355	3525	7	Cast iron	22	23	65	23	SPC355X4-FEN
375	3525	7	Cast iron	22	23	65	23	SPC375X4-FEN
400	3525	5	Cast iron	22	23	65	23	SPC400X4-FEN
425	3525	5	Cast iron	22	23	65	23	SPC425X4-FEN
450	3525	5	Cast iron	22	23	65	23	SPC450X4-FEN
475	3525	5	Cast iron	22	23	65	23	SPC475X4-FEN
500	3525	5	Cast iron	22	23	65	23	SPC500X4-FEN
560	3525	5	Cast iron	22	23	65	23	SPC560X4-FEN
630	4030	4	Cast iron	22	17.5	76	17.5	SPC630X4-FEN
800	5040	4	Cast iron	22	4.5	102	4.5	SPC800X4-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.