



FENNER V-pulley for taper bush section SPC - 8 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 8

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
74	65	74
68.5	76	68.5
62	89	62
55.5	102	55.5

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
200	3525	3	Cast iron	22	74	65	74	SPC200X8-FEN
212	3525	3	Cast iron	22	74	65	74	SPC212X8-FEN
236	3525	3	Cast iron	22	74	65	74	SPC236X8-FEN
250	3525	3	Cast iron	22	74	65	74	SPC250X8-FEN
280	3525	3	Cast iron	22	74	65	74	SPC280X8-FEN
300	3525	7	Cast iron	22	74	65	74	SPC300X8-FEN
315	3525	7	Cast iron	22	74	65	74	SPC315X8-FEN
335	3525	7	Cast iron	22	74	65	74	SPC335X8-FEN
355	3525		Cast iron	22				SPC355X8-FEN
375	4030	7	Cast iron	22	68.5	76	68.5	SPC375X8-FEN
400	4030	7	Cast iron	22	68.5	76	68.5	SPC400X8-FEN
425	4535	7	Cast iron	22	62	89	62	SPC425X8-FEN
450	4535	7	Cast iron	22	62	89	62	SPC450X8-FEN
475	4535	7	Cast iron	22	62	89	62	SPC475X8-FEN
500	4535	7	Cast iron	22	62	89	62	SPC500X8-FEN
530	4535	7	Cast iron	22	62	89	62	SPC530X8-FEN
560	4535	5	Cast iron	22	62	89	62	SPC560X8-FEN
630	4535	5	Cast iron	22	62	89	62	SPC630X8-FEN
800	5040	5	Cast iron	22	55.5	102	55.5	SPC800X8-FEN
1000	5040	5	Cast iron	22	55.5	102	55.5	SPC1000X8-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.