

FENNER HTD Timing belt section 8M belt width 50



Fenner HTD drive systems conform to ISO 13050 and have a curvilinear tooth form giving more uniform distribution of shear stresses within the teeth. Tooth loads are subsequently carried by the tensile members of the belt thus providing a significant improvement over Classical Timing belts.

Characteristics

Series: HTD

Type: 8M-050

Pitch length mm	Width mm	Pitch mm	Material	Article
480	50	8	CR	480-8M50-FEN
600	50	8		600-8M50-FEN
640	50	8		640-8M50-FEN
720	50	8	CR	720-8M50-FEN
800	50	8	CR	800-8M50-FEN
880	50	8	CR	880-8M50-FEN
920	50	8		920-8M50-FEN
960	50	8	CR	960-8M50-FEN
1040	50	8		1040-8M50-FEN
1120	50	8		1120-8M50-FEN
1200	50	8	CR	1200-8M50-FEN
1280	50	8	CR	1280-8M50-FEN
1360	50	8		1360-8M50-FEN
1424	50	8		1424-8M50-FEN
1440	50	8		1440-8M50-FEN
1600	50	8		1600-8M50-FEN
1760	50	8	CR	1760-8M50-FEN
1800	50	8	CR	1800-8M50-FEN
2000	50	8		2000-8M50-FEN
2400	50	8	CR	2400-8M50-FEN
2600	50	8	CR	2600-8M50-FEN
2800	50	8	CR	2800-8M50-FEN
3048	50	8		3048-8M50-FEN
3280	50	8		3280-8M50-FEN
3600	50	8		3600-8M50-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.