FENNER HTD Timing belt section 14M belt width 85



Fenner HTD drive systems conform to ISO 13050 and have a curvilinear tooth form giving more uniform distribution of shear stresses within the teeth. Tooth loads are subsequently carried by the tensile members of the belt thus providing a significant improvement over Classical Timing belts.

Characteristics

Series: HTD **Type:** 14M-085

Pitch length	Width	Pitch	Material	Article
mm	mm	mm		
966	85	14	CR	966-14M85-FEN
1190	85	14	CR	1190-14M85-FEN
1400	85	14	CR	1400-14M85-FEN
1610	85	14	CR	1610-14M85-FEN
1778	85	14	CR	1778-14M85-FEN
1890	85	14	CR	1890-14M85-FEN
2100	85	14	CR	2100-14M85-FEN
2310	85	14		2310-14M85-FEN
2450	85	14	CR	2450-14M85-FEN
2590	85	14	CR	2590-14M85-FEN
2800	85	14	CR	2800-14M85-FEN
3150	85	14	CR	3150-14M85-FEN
3360	85	5		3360-14M85-FEN
3500	85	14	CR	3500-14M85-FEN
3850	85	14	CR	3850-14M85-FEN
4326	85	14	CR	4326-14M85-FEN
4578	85	14	CR	4578-14M85-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: drives.support@eriks.co.uk

PR2277168452067903_EN_06.05.2024